


INSULATED BOOTLACE FERRULES

2620.0

H 0.25/10, 0.25 x 10mm Ferrule, Light Blue

- Funnel feed-in made of polypropylene
- Heat resistant up to 120 °C
- For wires from 0.5...150 mm²
- Material: E-Cu/A-Cu, galvanically tin-plated



PRODUCT DESCRIPTION

If the individual strands at the ends of finely stranded wires need to be protected due to frequent connecting, then our CONTA-CLIP wire-end ferrules are an ideal solution. The ferrules must be crimped gas-tight with the ends of the wires. A simply distortion caused by the clamping force is not adequate. The wire-end ferrules can be crimped easily and securely with CONTA-CLIP crimping pliers. The resulting connections function properly both electrically and mechanically.

- Collar feed-in made of polypropylene
- Heat resistant up to 120 °C
- For wires from 0.5-150 mm²
- Material: E-Cu/A-Cu, galvanically tin-plated

TECHNICAL DATA

GENERAL DATA

Standard	German Standard
Colour	Light blue
Rated wire cross section to (AWG)	24
Cross section max	0,25 mm ²

DIMENSIONS

Thickness of tube	0,15 mm
Thickness of collar	0,25 mm
Length	12 mm
Diameter of tube	0,85 mm

Stripping length	8 mm
Length of tube	6 mm
Diameter of collar	1,8 mm

MATERIALS

Operating temperature from	-5 °C
Plastic collar	Polypropylene-homopolymer
Operating temperature to	105 °C
Contact surface	Galvanic tin-plated, shiny
Conductor tube	Copper alloy

APPROVALS

DIN 46228-4:1990	Yes
DIN 46228-1:1992	No

ADDITIONAL DATA

Pack size	500
Country of origin	DE
Tariff code	85369010
Weight	0,06 g

