


INSULATED BOOTLACE FERRULES
0.14MM² TO 4MM²

V30AE001669

0.14mm² x 6mm Ferrule - Brown

- Funnel feed-in made of polypropylene
- Heat resistant up to 120 °C
- For wires from 0.14...4 mm²
- Material: E-Cu/A-Cu, galvanically tin-plated

**PRODUCT DESCRIPTION**

When the individual strands at the ends of finely stranded wires need to be protected and to provide a more robust connection, then our Z + F wire-end bootlace ferrules are an ideal solution.

The wire-end ferrules can be crimped easily and securely with Z + F crimping pliers or a variety of machines. The resulting connections function properly both electrically and mechanically.

European manufactured, this range ensures a reliable crimp without splitting.

TECHNICAL DATA**GENERAL DATA**

Standard	French Standard
Colour	Brown
Rated wire cross section to (AWG)	26
Cross section max	0,14 mm ²

DIMENSIONS

Thickness of tube	0,15 mm
Thickness of collar	0,25 mm
Length	10 mm
Diameter of tube	0,85 mm
Stripping length	8 mm
Length of tube	6 mm

Diameter of collar	1,8 mm
--------------------	--------

MATERIALS

Operating temperature from	-5 °C
Plastic collar	Polypropylene-homopolymer
Operating temperature to	105 °C
Contact surface	Galvanic tin-plated, shiny
Conductor tube	Copper alloy

APPROVALS

DIN 46228-4:1990	Yes
DIN 46228-1:1992	No

ADDITIONAL DATA

Pack size	500
Country of origin	DE
Tariff code	85369010
Weight	0,06 g

