


**INSULATED BOOTLACE FERRULES
6MM² TO 150MM²**

V30AE000025

6mm² x 12mm Ferrule - Black

- Funnel feed-in made of polypropylene
- Heat resistant up to 120 °C
- For wires from 6...150 mm²
- Material: E-Cu/A-Cu, galvanically tin-plated

**PRODUCT DESCRIPTION**

When the individual strands at the ends of finely stranded wires need to be protected and to provide a more robust connection, then our Z + F wire-end bootlace ferrules are an ideal solution.

The wire-end ferrules can be crimped easily and securely with Z + F crimping pliers or a variety of machines. The resulting connections function properly both electrically and mechanically.

European manufactured, this range ensures a reliable crimp without splitting.

TECHNICAL DATA**GENERAL DATA**

Standard	German Standard
Colour	Black
Rated wire cross section to (AWG)	10
Cross section max	6 mm ²

DIMENSIONS

Thickness of tube	0,2 mm
Thickness of collar	0,3 mm
Length	20 mm
Diameter of tube	3,5 mm
Stripping length	14 mm
Length of tube	12 mm

Diameter of collar	6,3 mm
---------------------------	--------

MATERIALS

Operating temperature from	-5 °C
-----------------------------------	-------

Plastic collar	Polypropylene-homopolymer
-----------------------	---------------------------

Operating temperature to	105 °C
---------------------------------	--------

Contact surface	Galvanic tin-plated, shiny
------------------------	----------------------------

Conductor tube	Copper alloy
-----------------------	--------------

APPROVALS

DIN 46228-4:1990	Yes
-------------------------	-----

DIN 46228-1:1992	No
-------------------------	----

ADDITIONAL DATA

Pack size	100
------------------	-----

Country of origin	DE
--------------------------	----

Tariff code	85369010
--------------------	----------

Weight	0,45 g
---------------	--------