


**INSULATED BOOTLACE FERRULE FOR  
DUAL CABLES**

V30AE006564

0.34mm<sup>2</sup> x 8mm Dual Ferrule - Cyan

- Funnel feed-in made of polypropylene
- Heat resistant up to 120 °C
- For wires from 0.5...16 mm<sup>2</sup>
- Material: E-Cu/A-Cu, galvanically tin-plated

**PRODUCT DESCRIPTION****TECHNICAL DATA****GENERAL DATA**

Standard	UL (DIN)/German Standard
Colour	Cyan
Rated wire cross section to (AWG)	22
Cross section max	0,34 mm <sup>2</sup>

**DIMENSIONS**

Thickness of tube	0,15 mm
Thickness of collar	0,25 mm
Length	15 mm
Diameter of tube	1,2 mm
Stripping length	11 mm
Length of tube	8 mm

**MATERIALS**

Operating temperature from	-5 °C
Plastic collar	Polypropylene-homopolymer

Operating temperature to	105 °C
Contact surface	Galvanic tin-plated, shiny
Conductor tube	Copper alloy

## APPROVALS

DIN 46228-4:1990	Yes
DIN 46228-1:1992	No

## ADDITIONAL DATA

Pack size	500
Country of origin	DE
Tariff code	85369010
Weight	0,14 g

