


**TRI-RATED INSULATED FERRULES  
0.5MM<sup>2</sup> TO 1.5MM<sup>2</sup> 16-20 AWG**

V30AE003544

0.5mm<sup>2</sup> x 8mm 20 AWG Ferrule - Orange

- Compatible with various international conductor standards.
- Made of durable tin-plated copper for reliability.
- Available in multiple sizes for diverse applications.
- Designed for easy installation in tight spaces.

**PRODUCT DESCRIPTION****TECHNICAL DATA****GENERAL DATA**

Standard	German Standard
Colour	Orange
Rated wire cross section to (AWG)	20
Cross section max	0,5 mm <sup>2</sup>

**DIMENSIONS**

Thickness of tube	0,15 mm
Thickness of collar	0,25 mm
Length	14 mm
Diameter of tube	1,1 mm
Stripping length	10 mm
Length of tube	8 mm
Diameter of collar	2,9 mm

**MATERIALS**

Operating temperature from	-5 °C
----------------------------	-------

<b>Plastic collar</b>	Polypropylene-homopolymer
<b>Operating temperature to</b>	105 °C
<b>Contact surface</b>	Galvanic tin-plated, shiny
<b>Conductor tube</b>	Copper alloy

## APPROVALS

<b>DIN 46228-4:1990</b>	Yes
<b>DIN 46228-1:1992</b>	No

## ADDITIONAL DATA

<b>Pack size</b>	500
<b>Country of origin</b>	EEC
<b>Tariff code</b>	85369010
<b>Weight</b>	0,09 g