OEM Automatic Ltd

Address: Whiteacres, Whetstone Leicester, LE8 6ZG 0116 284 9900 | Orders@oem.co.uk | www.oem.co.uk

VERTICAL MOUNT MINI HORN WITH BEACON, K SERIES

710011005 Mini horn + beacon, Amber, 24 V dc, KDL

- Vertical mount signal horn with beacon
- 88-92 dB Range
- Steady or Flashing light options



PRODUCT DESCRIPTION

The K series of signal horns give a tough, high quality option for visual and audible signalling.

- Combination of an electromechanical horn with signal beacon or strobe beacon
- For universal visual-audible applications
- Signal beacon Ø 60 mm
- Beacon options:
 - steady light with bulb or LED bulb (LLL)
 - flashing light with LED bulb (LLB)
- Models with or without cone
- Sound and light separately switchable
- Attractive price/performance ratio
- 2 mounting widths

TECHNICAL DATA

Diameter	75 mm
Flash energy	1 J
Flash frequency	2 Hz
IP class	IP43, NEMA Type 2
Lens colour	Orange
Light type	Bulb, LED
Number of tones	1
Sound level max	92 dB
Supply voltage	24 V

Temperature operational max	50 °C
Temperature operational min	-20 °C
Terminal connection	2,5 mm²
Weight	220 g

