



## SIGNAL TOWER Ø 70MM ECO

900011405

LED Steady, Amber, 24 V ac/dc, XDC

- Modular signal tower
- Integrated LED or filament bulb
- Wide control voltage range



### PRODUCT DESCRIPTION

The ECO range of modular signal towers uses the highest quality components and the latest technology but at an affordable price,

- Modular signal tower series in diameters Ø 70 mm, 60 mm and 40 mm for universal applications
- Modern signal tower concept based on up-to-date LED technique, alternative operation with conventional incandescent bulb technique
- Excellent cost/performance ratio
- Complete range of bright LED modules in function modes
- LED steady light
- LED flashing light
- LED strobe light (single flash)
- LED multi strobe light (multi flash)
- LED steady/LED strobe and LED multi strobe modules
- Very long lifetime due to maintenance free LED technique, vibration proof and significantly reduced nominal current
- Piezo buzzer and multi tone siren modules
- Easy to wire connections
- Comprehensive range of mounting options including quick mount solutions
- Plc fit (leakage and inrush current)
- High ingress protection IP 66 certified to UL type 4/4X/13

### TECHNICAL DATA

#### DATA

<b>Lens colour</b>	Orange
<b>IP class</b>	IP66
<b>Light source</b>	LED
<b>Light type</b>	Orange LED
<b>Supply voltage</b>	24 V
<b>Mounting</b>	Bayonet
<b>Nominal current max</b>	0,054 A
<b>Temperature operational min</b>	-30 °C
<b>Temperature operational max</b>	60 °C
<b>Weight</b>	100 g

Supply voltage ac/dc min	21,6 V
Supply voltage ac/dc max	26,4 V
Nominal current min	0,049 A
Number of optional modules	2
Diameter	70 mm





