



MT60 MONOLITHIC SIGNAL TOWER

MT60-F100-24V DC

24 V DC red/yellow/green, white with tube base

- Pre-assembled entry level signal tower for ready-to-go installation
- Excellent circular light distribution to prevent blind spots
- Transparent lens to prevent wrong signaling indication caused by external light interferences
- Easy cleaning of the monolithic single lens also powerful water jets possible (IP66)
- Fixed, seperared colour positions(green/yellow/red) with steady light and escalation options, including flashing red and/or sound



PRODUCT DESCRIPTION

Introducing Auer's pre-assembled entry-level signal tower, designed for ready-to-go installation with minimal setup. This signal tower features excellent circular light distribution, eliminating blind spots and ensuring clear visibility from all angles. The transparent lens is engineered to prevent incorrect signalling caused by external light interference, and its monolithic design allows for easy cleaning, even with powerful water jets (IP66 rated). With fixed, separated colour positions for green, yellow, and red, the tower offers steady light and escalation options, including flashing red and optional sound alerts, to meet various signalling needs effectively.

TECHNICAL DATA

DATA

Lens colour	White
Housing Colour	White
IP class	IP66
Mounting	Pipe socket
Temperature operational min	-25 °C
Temperature operational max	50 °C
Nominal current	3 mA
IK class	7
Nominal Supply Voltage	24 V DC
Diameter	61 mm
Height	291 mm

INPUT				
MT2 Male Connector PIN	Terminal block Input	MT60-F100-... MT60-W-...	MT60-M12-24V DC	MT60-M12-S-24V DC
3	0	common	common	common
4	1	green steady	green steady	green steady
1	2	yellow steady	yellow steady	yellow steady
2	3	red steady	red steady	red steady
5	4	red blinking	red blinking	tone pulsing
	6	tone pulsing (optional)	-	-

MT60 Dimension Drawing

