0116 284 9900 | Orders@oem.co.uk | www.oem.co.uk

# **ORLACO 12 INCH MONITORS**

ORL0411200 Set monitor 12" RLED CAN

- 12-30 V DC
- Operating temperature -40 to +85 ° C
- Cast contacts
- Resolution XGA 1024xRGBx768 pixels





## PRODUCT DESCRIPTION

Orlaco's 12 "monitors are IP67-rated. They also have automatic light adjustment. The 12" monitor fits perfectly when you want to see more than one image at a time. For example, when you want to use Orlaco's "Surroundview".

# **TECHNICAL DATA**

Attachment	RAM 190 mm
Cable length	6000 mm
Contacts	7-pole
Display size	12 "
Image format	4:3
IP class	IP67
Supply voltage dc max	30 V DC
Supply voltage dc min	18 V DC
Temperature operational max	85 °C
Temperature operational min	-40 °C
Туре	Analogue
Vibration resistance	50g
Video cable	6000 mm



Electrical connection

Connections to the monitor: (Secure the power input with a 5A fuse)

1 = Red = Power input 12...30V

2 = White = Power input 00

3 = Blue = Gam No. 1 activated at 12...30V

5 = White/Yellow = Cam No. 2 activated at 12...30V

6 = Grey = Aux 1 activated at 12...30V

7 = Yellow = Aux 2 activated at 12V...30V

Shelding = To GND



Front side molded 4p female connector:

1 = Coax core = Video input
2 = Coax shielding = Video 0V
3 = Red = Power output: 12...30V
4 = Black = Power output: 0V
Shielding = To housing



