

0116 284 9900 | Orders@oem.co.uk | www.oem.co.uk

ORLACO FAMOS CAMERA

ORL0171070 Camera FAMOS 170° PAL

- Robust construction for extreme environments
- 12 or 24 V DC
- operating temperature -40 to +85 °C
- · Epoxy-filled, better protection against moisture



ORLACO°

PRODUCT DESCRIPTION

These cameras are available in several different viewing angles to suit the various applications they can be used in. For example, if you want to see details in a long way, choose a narrower opening angle and instead you want a cross-section view, choose a further opening angle. Orlaco cameras are suitable for all types of vehicles, regardless of whether you need a power camera, back camera or side camera.

Orlaco's new FAMOS camera is not gas-filled as the traditional clover camera has been before, but it's epoxy-filled instead. This has provided better protection against moisture.

TECHNICAL DATA

Camera angle	170 °
Contacts	4-pole male
Image format	PAL
IP class	IP68, IP69K
Supply voltage dc max	24 V DC

Supply voltage dc min	12 V DC
Temperature operational max	85 °C
Temperature operational min	-40 °C
Vibration resistance	50g



 Electrical connections

 Front side of molded 4p male connector

 1 = Coax core
 = Video signal

 2 = Coax screen
 = Video GND

 3 = Red
 = 12...24V/DC

 4 = Black/orange
 = OV

 Shielding
 To connector housing

