

ORLACO MULTI CABLE

ORL0301960

Cable 1m UNI 4P Molded Connector

- 4-pole and 7-pole M16 cast contacts
- Developed by Orlaco for best EMC protection
- -40 to +85 °C

**PRODUCT DESCRIPTION**


Orlaco develops its own cabling for the best possible image and EMC protection. Molded contacts make them well protected from moisture.

The multi cable is intended for static mounting.


If you would like a cabling to be used for a mobile application, take a look at the range of our Dynamic Cabling.

TECHNICAL DATA

Cable diameter	6 mm
Cable length	1000 mm
IP class	IP67
Material	PVC
Temperature operational max	85 °C
Temperature operational min	-40 °C
Type	Analogue




Front side female connector




Front side male connector

Electrical connection

- 1 = Coax core = Video signal
- 2 = Coax shielding = Video GND
- 3 = Red = 12V/DC
- 4 = Black = 0V
- Shielding = GND



Front side molded 7P Female connector



Front side molded 7P Male connector

Electrical connection molded connectors

- 1 = Coax Core
- 2 = Coax Shield
- 3 = Red (Power input)
- 4 = Black (0V)
- 5 = Orange (Rx)
- 6 = Yellow (Tx)
- 7 = Grey (Aux)

Dimensions

